



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
|-----------------|-------------|----------------------|---------------------|------------------|

10/026,944

12/27/2001

Ari Hottinen

060258-0290575

7322

909

7590

09/02/2008

PILLSBURY WINTHROP SHAW PITTMAN, LLP
P.O. BOX 10500
MCLEAN, VA 22102

EXAMINER

DEAN, RAYMOND S

ART UNIT

PAPER NUMBER

2618

MAIL DATE

DELIVERY MODE

09/02/2008

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

| | | | |
|------------------------------|--------------------------------------|--------------------------------------|--|
| Office Action Summary | Application No. 10/026,944 | Applicant(s) HOTTINEN, ARI | |
| | Examiner RAYMOND S. DEAN | Art Unit 2618 | |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 12 May 2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-11, 14-32 and 34-41 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-11, 14-32 and 34-41 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 02 November 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed May 12, 2008 regarding Muller lacking the probability distribution feature have been fully considered but they are not persuasive.

Examiner respectfully disagrees with Applicants' assertion on Page 12, 3rd Paragraph "but Muller clearly does not teach or suggest calculating a probability ...". Column 5 lines 5 – 25 of Muller shows that the probability measure, which is the FER, is taken or made periodically in order to control the target for the inner loop power control. Since the FER is taken periodically there will be a plurality of frames, in which the measurement of the FER is taken, and a plurality of FER measurements. Since there is a plurality of FER measurements there is thus a distribution of FER measurements. This distribution enables the target for the inner loop power control to be set, thus ultimately causing the determination of the type of power control commands to be used. Muller thus reads on the limitation in question.

2. Applicant's arguments, see remarks filed May 12, 2008 regarding the step size limitation in now cancelled Claims 4 and 25 have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of newly cited prior art Baker et al. (US 6,754,505).

Baker, which also teaches inner and outer loop power control, teaches step-like power control commands configured such that a step size depends on the estimated reliability (Col. 4 lines 26 – 27, lines 37 – 44, the estimated reliability is the quality metric).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the above power control method of Baker as an alternative means for achieving the predictable result of inner loop power control and for the purpose of preventing the corruption of data transmission that occurs due to the delay in the convergence of the power control loops as taught by Baker.

Claim Rejections - 35 USC § 103

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 1 – 3, 5 – 10, 18, 22 – 24, 26 – 31, 34, and 37 - 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) and in further view of Baker et al. (US 6,754,505)

Regarding Claim 1, Muller teaches a method for implementing power control on a connection between two transceivers, the method comprising receiving frame-structured signal sent from the first transceiver using the second transceiver (Column 5 lines 1 – 4,

Art Unit: 2618

there is a measurement of the FER thus there will be a frame-structured signal), decoding the received signal in a decoder of the second transceiver, the decoder providing a soft decision estimate concerning the reliability of the signal in the output thereof (Figure 2, Column 1 lines 66 – 67, Column 2 lines 23 – 28, Column 4 lines 56 – 60, Column 4 lines 50 – 51, the data processing and control unit decodes the signal received at the base station thus there will be inherent decoding circuitry in said data processing and control unit, the reliability of the signal is measured in E_{b/I_o}), estimating the error probability for a given number of bits in a frame for the received signal on the basis of CRC calculations and comparisons (Column 5 lines 5 – 8, lines 26 – 29, the FER is a probability of error, the FER comprises a measure of the bits in a frame that are in error), comparing the estimated probability or the parameter modeling the probability to a particular given threshold value (Column 4 lines 56 – 67, Column 5 lines 14 - 20), adjusting the transmission power of the first transceiver in the second transceiver by signaling power control information to the first transceiver so that the estimated probability is as close as possible to the given probability, wherein the power control information is calculated on the basis of the estimated probability (Figure 5, Column 4 lines 56 – 67, Column 5 lines 14 – 20).

Muller does not teach estimating the error probability for a given number of bits in a frame for the received signal on the basis of soft decisions provided by the decoder and wherein the power control information signaled to the first transceiver comprises step-like power control commands configured such that a step size depends on the estimated reliability.

Hosur teaches estimating an error for a given number of bits for a received signal on the basis of soft decisions by a Viterbi decoder (Col. 6 lines 37 – 44, viterbi decoders can be hard decision type or soft decision type, the soft decision type decoders receive bitstreams containing information about the reliability of each received symbol, the output of the viterbi decoder in Hosur is used to estimate the FER, which is a reliability metric, thus the Viterbi decoder is acting as a soft decision type decoder).

Muller teaches the use of a Viterbi decoder for signal processing (Column 4 lines 50 – 51) thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the Viterbi decoder taught by Hosur as an alternative means for error measurements thereby providing a means for error correction as taught by Hosur.

Baker, which also teaches inner and outer loop power control, teaches step-like power control commands configured such that a step size depends on the estimated reliability (Col. 4 lines 26 – 27, lines 37 – 44, the estimated reliability is the quality metric).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the above power control method of Baker as an alternative means for achieving the predictable result of inner loop power control and for the purpose of preventing the corruption of data transmission that occurs due to the delay in the convergence of the power control loops as taught by Baker.

Regarding Claim 2, Muller teaches a method for implementing power control on a connection between two transceivers, the method comprising receiving frame-structured

Art Unit: 2618

signal sent from the first transceiver using the second transceiver (Column 5 lines 1 – 4, there is a measurement of the FER thus there will be a frame-structured signal), decoding the received signal in a decoder of the second transceiver, the decoder providing a soft decision estimate concerning the reliability of the signal in the output thereof (Figure 2, Column 1 lines 66 – 67, Column 2 lines 23 – 28, Column 4 lines 56 – 60, Column 4 lines 50 – 51, the data processing and control unit decodes the signal received at the base station thus there will be inherent decoding circuitry in said data processing and control unit, the reliability of the signal is measured in E_{b/I_o}), estimating the error probability for a given number of bits in a frame for the received signal on the basis of CRC calculations and comparisons (Column 5 lines 5 – 8, lines 26 – 29, the FER is a probability of error, the FER comprises a measure of the bits in a frame that are in error), comparing the estimated probability or the parameter modeling the reliability to a particular given threshold value (Column 4 lines 56 – 67, Column 5 lines 14 – 20), adjusting the transmission power of the first transceiver in the second transceiver by signaling power control information to the first transceiver so that the estimated probability is as close as possible to the given probability (Figure 5, Column 4 lines 56 – 67, Column 5 lines 14 – 20), wherein an estimate of at least one probability measure distribution is generated using the probability measures of several received frames, and the power control information is calculated on the basis of the estimated probability (Column 4 lines 56 – 67, Column 5 lines 14 – 20).

Muller does not teach estimating the error probability for a given number of bits in a frame for the received signal on the basis of soft decisions provided by the decoder

Art Unit: 2618

and wherein the power control information signaled to the first transceiver comprises step-like power control commands configured such that a step size depends on the estimated reliability.

Hosur teaches estimating an error for a given number of bits for a received signal on the basis of soft decisions by a Viterbi decoder (Col. 6 lines 37 – 44, viterbi decoders can be hard decision type or soft decision type, the soft decision type decoders receive bit streams containing information about the reliability of each received symbol, the output of the viterbi decoder in Hosur is used to estimate the FER, which is a reliability metric, thus the Viterbi decoder is acting as a soft decision type decoder).

Muller teaches the use of a Viterbi decoder for signal processing (Column 4 lines 50 – 51) thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the Viterbi decoder taught by Hosur as an alternative means for error measurements thereby providing a means for error correction as taught by Hosur.

Baker, which also teaches inner and outer loop power control, teaches step-like power control commands configured such that a step size depends on the estimated reliability (Col. 4 lines 26 – 27, lines 37 – 44, the estimated reliability is the quality metric).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the above power control method of Baker as an alternative means for achieving the predictable result of inner loop power control and for the

Art Unit: 2618

purpose of preventing the corruption of data transmission that occurs due to the delay in the convergence of the power control loops as taught by Baker.

Regarding Claim 3, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein the given threshold value is adjusted in order to optimize signal quality in a step like fashion so that the step size depends on the estimated reliability (Column 5 lines 14 – 20, Column 6 lines 17 - 31).

Regarding Claim 5, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein the desired transmission power is signaled in such a manner that the power depends on the estimated reliability (Column 4 lines 56 – 67).

Regarding Claim 6, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein an estimate concerning the bit error rate of the signal is obtained from the decoder (Column 5 lines 5 – 8).

Regarding Claim 7, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein an estimate concerning the bit error rate of the frame bits is obtained from the decoder (Column 5 lines 39 – 43).

Regarding Claim 8, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein an

Art Unit: 2618

estimate concerning the frame error rate of the signal is obtained from the decoder (Column 5 lines 5 – 8).

Regarding Claim 9, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein signal credibility metric is obtained from the decoder (Column 4 lines 56 – 60, E sub b/I sub o also gives a measure of the signal credibility).

Regarding Claim 10, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller further teaches wherein the step size depends on the estimated reliability and on the reliability requirement set on the connection (Column 4 lines 56 – 67).

Regarding Claim 14, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 1 or 2. Muller further teaches wherein the values obtained in CRC calculation are used together with the reliability values in connection with the adjustment (Column 5 lines 26 – 32).

Regarding Claim 18, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 2. Muller further teaches wherein at least two reliability metric distributions are calculated, where different distributions correspond with different signal statistics at the input of the decoder (Column 5 lines 5 – 8, Column 5 lines 14 – 20, the FER and BER are also reliability metrics, the distributions of said FER and BER will inherently be different since they represent frame errors and bit errors respectively, since their distributions will be different their signal statistics will be different).

Regarding Claim 22, Muller teaches an arrangement for implementing power control on a connection between two transceivers, the arrangement comprising in the second transceiver means for receiving frame-structured signal sent from the first transceiver using the second transceiver (Column 5 lines 1 – 4, there is a measurement of the FER thus there will be a frame-structured signal), means for decoding the received signal, the means being arranged to provide a soft decision estimate concerning the reliability of the signal in the output thereof (Figure 2, Column 1 lines 66 – 67, Column 2 lines 23 – 28, Column 4 lines 56 – 60, Column 4 lines 50 – 51, the data processing and control unit decodes the signal received at the base station, the reliability of the signal is measured in E_b/I_o), means for establishing the error probability for a given number of bits in a frame for the received signal on the basis of CRC calculations and comparisons (Column 5 lines 5 – 8, lines 26 – 29, the FER is a probability of error, the FER comprises a measure of the bits in a frame that are in error), means for comparing the estimated probability or the parameter modeling the reliability to a particular given threshold value (Column 4 lines 56 – 67, Column 5 lines 14 – 20), means for adjusting the transmission power of the first transceiver in the second transceiver by forming and signaling power control information to the first transceiver so that the estimated probability is as close as possible to the given probability (Column 4 lines 56 – 67, Column 5 lines 14 – 20), means for adjusting the given threshold value in order to optimize signal quality (Column 5 lines 14 – 20), and means for calculating the power control information on the basis of the estimated probability (Column 4 lines 56 – 67, Column 5 lines 14 – 20).

Muller does not teach means for establishing the error probability for a given number of bits in a frame for the received signal on the basis of soft decisions provided by the decoder and wherein the means for calculating power control information signals step-like power control commands to the first transceiver such that a step size depends on the estimated signal reliability.

Hosur teaches means for establishing an error measurement for a given number of bits for a received signal on the basis of soft decisions by a Viterbi decoder (Col. 6 lines 37 – 44, viterbi decoders can be hard decision type or soft decision type, the soft decision type decoders receive bit streams containing information about the reliability of each received symbol, the output of the viterbi decoder in Hosur is used to estimate the FER, which is a reliability metric, thus the Viterbi decoder is acting as a soft decision type decoder).

Muller teaches the use of a Viterbi decoder for signal processing (Column 4 lines 50 – 51) thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the Viterbi decoder taught by Hosur as an alternative means for error measurements thereby providing a means for error correction as taught by Hosur.

Baker, which also teaches inner and outer loop power control, teaches step-like power control commands such that a step size depends on the estimated signal reliability (Col. 4 lines 26 – 27, lines 37 – 44, the estimated reliability is the quality metric).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the above power control method of Baker as an alternative means for achieving the predictable result of inner loop power control and for the purpose of preventing the corruption of data transmission that occurs due to the delay in the convergence of the power control loops as taught by Baker.

Regarding Claim 23, Muller teaches an arrangement for implementing power control on a connection between two transceivers, the arrangement comprising in the second transceiver means for receiving frame-structured signal sent from the first transceiver using the second transceiver (Column 5 lines 1 – 4, there is a measurement of the FER thus there will be a frame-structured signal), decoding the received signal in a decoder of the second transceiver, means for decoding the received signal, the means being arranged to provide a soft decision estimate concerning the reliability of the signal in the output thereof (Figure 2, Column 1 lines 66 – 67, Column 2 lines 23 – 28, Column 4 lines 56 – 60, Column 4 lines 50 – 51, the data processing and control unit decodes the signal received at the base station, the reliability of the signal is measured in E_{b/I_o}), means for estimating the error probability for a given number of bits in a frame for the received signal on the basis of CRC calculations and comparisons (Column 5 lines 5 – 8, lines 26 – 29, the FER is a probability of error, the FER comprises a measure of the bits in a frame that are in error), means for comparing the estimated probability or the parameter modeling the probability to a particular given threshold value (Column 4 lines 56 – 67, Column 5 lines 14 – 20), means for adjusting the transmission power of the first transceiver in the second transceiver by forming and

Art Unit: 2618

signaling power control information to the first transceiver so that the estimated probability is as close as possible to the given probability (Column 4 lines 56 – 67, Column 5 lines 14 - 20), means for generating an estimate of at least one probability measure distribution using the probability measures of several received frames, and means for calculating the power control information on the basis of the estimated probability (Column 4 lines 56 – 67, Column 5 lines 14 – 20).

Muller does not teach means for estimating the error probability for a given number of bits in a frame for the received signal on the basis of soft decisions provided by the decoder and wherein the means for calculating power control information signals step-like power control commands to the first transceiver such that a step size depends on the estimated signal reliability

Hosur teaches means for estimating an error for a given number of bits for a received signal on the basis of soft decisions by a Viterbi decoder (Col. 6 lines 37 – 44, viterbi decoders can be hard decision type or soft decision type, the soft decision type decoders receive bit streams containing information about the reliability of each received symbol, the output of the viterbi decoder in Hosur is used to estimate the FER, which is a reliability metric, thus the Viterbi decoder is acting as a soft decision type decoder).

Muller teaches the use of a Viterbi decoder for signal processing (Column 4 lines 50 – 51) thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the Viterbi decoder taught by Hosur as an alternative means

Art Unit: 2618

for error measurements thereby providing a means for error correction as taught by Rick.

Baker, which also teaches inner and outer loop power control, teaches step-like power control commands such that a step size depends on the estimated signal reliability (Col. 4 lines 26 – 27, lines 37 – 44, the estimated reliability is the quality metric).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the above power control method of Baker as an alternative means for achieving the predictable result of inner loop power control and for the purpose of preventing the corruption of data transmission that occurs due to the delay in the convergence of the power control loops as taught by Baker.

Regarding Claim 24, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the means adjust the given threshold value in order to optimize in a step like fashion so that the step size depends on the estimated reliability (Column 5 lines 14 – 20, Column 6 lines 17 - 31).

Regarding Claim 26, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the means signal the desired power control so that the power depends on the estimated reliability (Column 4 lines 56 – 67).

Regarding Claim 27, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the

Art Unit: 2618

output of the decoding means comprise an estimate concerning the bit error rate of the frame bits (Column 5 lines 39 – 43).

Regarding Claim 28, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the output of the decoding means comprise an estimate concerning the bit error rate of the signal (Column 5 lines 5 – 8).

Regarding Claim 29, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the output of the decoding means comprise an estimate concerning the frame error rate of the signal (Column 5 lines 5 – 8).

Regarding Claim 30, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the output of the decoding means comprise signal credibility metric (Column 4 lines 56 – 60, E sub b/I sub o also gives a measure of the signal credibility).

Regarding Claim 31, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the means control the power control in such a manner that the step size depends on the estimated reliability and on the reliability requirement set on the connection. (Column 4 lines 56 – 67).

Regarding Claim 34, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the

Art Unit: 2618

means utilize the values obtained in CRC calculation for calculating the reliability (Column 5 lines 26 – 32).

Regarding Claim 37, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller further teaches wherein the means control the power control in such a manner that the combination of the reliability metrics of consecutive frames should be kept at a desired level (Column 4 lines 56 – 67, the frames comprise time slots which means that there will be pilot symbols in said frames and thus several measurements of E_{b/I_o} such that the mobile station transmit power is constantly adjusted to meet the desired level, which is the target E_{b/I_o}).

Regarding Claim 38, Muller in view of Hosur in further view of Baker teaches all of the claimed limitations recited in Claim 23. Muller further teaches wherein the means calculate at least two reliability metric distributions where different distributions correspond with different signal statistics at the input of the decoder (Column 5 lines 5 – 8, Column 5 lines 14 – 20, the FER and BER are also reliability metrics, the distributions of said FER and BER will inherently be different since they represent frame errors and bit errors respectively, since their distributions will be different their signal statistics will be different).

5. Claims 11 and 32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) in view of Baker et al.

Art Unit: 2618

(US 6,754,505) as applied to Claims 1, 22 above, and further in view of Tong et al. (US 6,311,070).

Regarding Claim 11, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller in view of Hosur and in further view of Baker does not teach wherein the step size is selected from a set of possible step sizes.

Tong teaches wherein the step size is selected from a set of possible step sizes (Table 3, Column 4 lines 46 – 57).

Muller in view of Hosur in further view of Baker and Tong teach a CDMA system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the set of possible sizes taught in Tong in the CDMA system of Muller in view of Hosur and in further view of Baker for the purpose of creating a power control system which: minimizes power overshoot, minimizes the standard deviation from the nominal power level, and maximizes uplink capacity as taught by Tong.

Regarding Claim 32, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means select the step size from a set of possible step sizes.

Tong teaches wherein the step size is selected from a set of possible step sizes (Table 3, Column 4 lines 46 – 57).

Muller in view of Hosur in further view of Baker and Tong teach a CDMA system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the set of possible sizes taught in Tong in the CDMA system of Muller in view of Hosur and in further view of Baker for the purpose of creating a power control system which: minimizes power overshoot, minimizes the standard deviation from the nominal power level, and maximizes uplink capacity as taught by Tong.

6. Claims 15 and 35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) in view of Baker et al. (US 6,754,505), as applied to Claims 1, 22 above, and further in view of Mitra et al. (5,732,328).

Regarding Claim 15, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller in view of Hosur and in further view of Baker does not teach wherein the reliability estimates enable to search for a step size that optimizes the BER outage probability.

Mitra teaches optimizing the BER outage probability (Column 4 lines 29 – 34).

Muller in view of Hosur in further view of Baker and Mitra teach a wireless system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use outage probability taught in Mitra in the wireless system of Muller in view of Hosur and in further view of Baker for the

purpose of determining a desired signal strength to be received by a base station that would likely produce signal outage intervals that are tolerable as taught by Mitra.

Regarding Claim 35, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means search for a step value that optimizes the BER outage probability using the reliability estimate.

Mitra teaches optimizing the BER outage probability (Column 4 lines 29 – 34).

Muller in view of Hosur in further view of Baker and Mitra teach a wireless system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use outage probability taught in Mitra in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of determining a desired signal strength to be received by a base station that would likely produce signal outage intervals that are tolerable as taught by Mitra.

7. Claims 16 - 17 and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) in view of Baker et al. (US 6,754,505), as applied to Claims 1, 22 above, and further in view of Denkert et al. (US 6,374,117).

Regarding Claim 16, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller in view of Hosur and in further view of Baker does not teach wherein the information to be sent in consecutive frames is at least partly similar.

Denkert teaches wherein the information to be sent in consecutive frames is at least partly similar (Column 6 lines 23 – 32, in a wireless system that uses ARQ there will be retransmission of data that was transmitted in the previous frame thus said data in the current frame will be similar to the data in the previous frame).

Muller in view of Hosur in further view of Baker and Denkert teach a frame based wireless system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to make a design preference and use the ARQ method taught in Denkert in the wireless system of Muller in view of Hosur and in further view of Baker as an alternative means for handling erroneously received information as taught by Denkert.

Regarding Claim 17, Muller in view of Hosur in view of Baker and further in view of Denkert teaches all of the claimed limitations recited in Claim 16. Muller further teaches wherein the combination of the reliability metrics of consecutive frames should be kept at a desired level (Column 4 lines 56 – 67, the frames comprise time slots which means that there will be pilot symbols in said frames and thus several measurements of $E_{\text{sub } b} / I_{\text{sub } o}$ such that the mobile station transmit power is constantly adjusted to meet the desired level, which is the target $E_{\text{sub } b} / I_{\text{sub } o}$).

Regarding Claim 36, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 22 or 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means receive frame-structured signal sent from the first transceiver where the information in the consecutive frames is at least partly similar.

Denkert teaches where the information in consecutive frames is at least partly similar (Column 6 lines 23 – 32, in a wireless system that uses ARQ there will be retransmission of data that was transmitted in the previous frame thus said data in the current frame will be similar to the data in the previous frame).

Muller in view of Hosur in further view of Baker and Denkert teach a frame based wireless system that incorporates power control thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to make a design preference and use the ARQ method taught in Denkert in the wireless system of Muller in view of Hosur and in further view of Baker as an alternative means for handling erroneously received information as taught by Denkert.

8. Claims 19 – 20 and 39 – 40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) in view of Baker et al. (US 6,754,505), as applied to Claims 1, 22, 23 above, and further in view of Shah (6,167,259).

Regarding Claim 19, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 2. Muller in view of Hosur and in further view of Baker does not teach wherein a non-parametric estimator is used for generating a reliability measure distribution.

Shah teaches a non-parametric estimator (Column 8 lines 19 – 27).

Muller in view of Hosur in further view of Baker and Shah teach a wireless system comprising forward and reverse links thus it would have been obvious to one of

Art Unit: 2618

ordinary skill in the art at the time the invention was made to use the non-parametric estimation taught in Shah in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of analyzing the BER on the forward and reverse links to quantify the degree of balance of said links.

Regarding Claim 20, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 2. Muller in view of Hosur and in further view of Baker does not teach wherein a parametric estimator is used for generating a reliability measure distribution.

Shah teaches a parametric estimator (Column 8 lines 19 – 27, the non-parametric estimator is used when the data distribution is not normal thus a parametric estimator will be used when said data distribution is normal).

Muller in view of Hosur in further view of Baker and Shah teach a wireless system comprising forward and reverse links thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the parametric estimation taught in Shah in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of analyzing the BER on the forward and reverse links to quantify the degree of balance of said links.

Regarding Claim 39, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means use a non-parametric estimator for generating the reliability measure distribution.

Shah teaches a non-parametric estimator (Column 8 lines 19 – 27).

Muller in view of Hosur in further view of Baker and Shah teach a wireless system comprising forward and reverse links thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the non-parametric estimation taught in Shah in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of analyzing the BER on the forward and reverse links to quantify the degree of balance of said links.

Regarding Claim 40, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means use a parametric estimator for generating the reliability measure distribution.

Shah teaches a parametric estimator (Column 8 lines 19 – 27, the non-parametric estimator is used when the data distribution is not normal thus a parametric estimator will be used when said data distribution is normal).

Muller in view of Hosur in further view of Baker and Shah teach a wireless system comprising forward and reverse links thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the parametric estimation taught in Shah in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of analyzing the BER on the forward and reverse links to quantify the degree of balance of said links.

9. Claims 21 and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Muller (US 6,490,461) in view of Hosur et al. (US 6,977,910) in view of Baker et al.

Art Unit: 2618

(US 6,754,505), as applied to Claims 1, 22, 23 above, and further in view of Gatherer et al. (US 2002/0115463).

Regarding Claim 21, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claims 1 or 2. Muller in view of Hosur and in further view of Baker does not teach wherein the reliability estimate depends on the a posteriori probabilities or likelihood values of the information bits obtained from the output of the decoder.

Gatherer teaches a posteriori probabilities of information bits (Section 0015 lines 5 – 10).

Muller in view of Hosur in further view of Baker and Gatherer teach a wireless system incorporates coding thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the a posteriori probabilities taught in Gatherer in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of producing an improved estimate of the received symbols as taught by Gatherer.

Regarding Claim 41, Muller in view of Hosur and in further view of Baker teaches all of the claimed limitations recited in Claim 22 or 23. Muller in view of Hosur and in further view of Baker does not teach wherein the means calculate a reliability estimator in such a manner that it depends on the a posteriori probabilities or likelihood values of the information bits to be obtained from the output of the decoder.

Gatherer teaches a posteriori probabilities of information bits (Section 0015 lines 5 – 10).

Art Unit: 2618

Muller in view of Hosur in further view of Baker and Gatherer teach a wireless system incorporates coding thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the a posteriori probabilities taught in Gatherer in the wireless system of Muller in view of Hosur and in further view of Baker for the purpose of producing an improved estimate of the received symbols as taught by Gatherer.

Conclusion

10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to RAYMOND S. DEAN whose telephone number is (571)272-7877. The examiner can normally be reached on Monday-Friday 6:00-2:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward F. Urban can be reached on 571-272-7899. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Raymond S Dean/
Primary Examiner, Art Unit 2618

Raymond S. Dean
August 28, 2008